

Beam Dynamics and Technologies for Future Colliders

 21 Feb 2018, 08:30 → 6 Mar 2018, 21:00 Europe/Zurich

 Hotel Crowne Plaza (Zurich, Switzerland)

14:30 → 15:20 **Linear Collider Studies Overview**

Speaker: Dr. Steinar STAPNES (CERN)

Main sources: talks by Shin Michizono, Akira Yamamoto, Phil Allport – and my old slides from various talks also full of “extractions” from many LC colleagues

More information for most topics will be given in your lectures the next two weeks



Experimental Particle Physics

Accelerators

- Luminosity, energy, quantum numbers, physics goals

Detectors

- Efficiency, speed, granularity, resolution, physics goals

Trigger/DAQ

- Efficiency, compression, through-put, physics models

Offline analysis

- Signal and background, physics studies

The primary factors for a successful experiment are the accelerator and detector trigger system, and losses there are not recoverable.

At all steps above simulations and real data are used



Particle type to accelerate

Not so many choices:



- Need stable charged particles: protons, electrons, (muons), ions – most used: electrons and protons
- Secondary beams: photons, pions, kaons, neutrons, neutrinos,

Proton collisions: compound particles

- Mix of quarks, anti-quarks and gluons: variety of processes
- Parton energy spread
- QCD processes large background sources

Electron/positron collisions: elementary particles


- Collision process known
- Well defined energy
- Background from other physics limited





$$\frac{\text{proton mass}}{\text{electron mass}} \approx 2000$$

The landscape

Quarks



Forces






Leptons



“Unknowns”:

- Flavour structure
- Matter-antimatter
- Why is the Higgs so light
- Neutrino sector
- Forces merging ?
- Gravity
- ...



Limitations - synchrotron radiation


We want E_{cm} as high as possible for new particle accelerators

Circular colliders \Rightarrow synchrotron radiation loss:

$$P_S = \frac{e^2 c}{6\pi\epsilon_0} \frac{1}{(m_0 c^2)^4} \frac{E^4}{R^2}$$

For electrons a severe limitation, size and costs explode – go linear

Less of a problem with protons (size of ring driven by magnet technology but radiation losses also there becoming significant for the components)




There are other reasons why linear colliders are pursued:

- Scalable (lengthen or shorten) and upgradable with new technology
- Very linked the main invest-area in accelerator construction – light-sources/FELs
- Affordable covering (most of) the Standard Model precision physics

Linear Collider (LC) studies – CLIC and ILC


Outline:

- Generic elements and challenges of a Linear Colliders
- Focus on CLIC (380 GeV) and ILC (250 GeV) status
- Smaller Linear Accelerators for material characterization, medical applications , etc
- Key points



Generic Linear Collider

The key parameters: Energy and luminosity






The critical steps (in next slides):

- 1) Create low emittance beams (sources, injector, damping rings, ring to main linac - RTML)
- 2) Acceleration in main linac (energy increase per length)
- 3) Supply energy as efficient as possible to beam (high power at 1, 1.3 and 12 GHz)
- 4) Nano-beams: Squeeze the beam (Beam Delivery System- BDS), i.e. reduce β

$$\mathcal{L} = H_D \frac{N^2}{4\pi\sigma_x\sigma_y} n_b f_r$$


$$\sigma_{x,y} = \sqrt{\frac{\beta_{x,y}\epsilon_{x,y}}{\gamma}}$$

Maximize acceleration per meter



Below left: A high-gradient “warm” accelerating structure, 12 GHz for CLIC

Above: A superconducting 1.3 GHz Rf structure for ILC



Limitations by electrical and magnetic fields on surfaces, field emission and heating (key technology optimisation)

Different pulse lengths and bunch structure (ILC and CLIC):


Parameter	ILC	CLIC
Bunches per pulse	n_b	312
Distance between bunches	Δz [mm]	0.5
Repetition rate	f_r [Hz]	50

... has ramifications for acc. size, beam dynamics, instrumentation, detectors, etc,


However, physics, cost, power, luminosities remarkably similar in the end (for similar collision energies)



RF power



Example: CLIC 20 MW L-band (1 GHz)
Multi-beam pulsed klystron.





Nano-beams

Very small beams (example from ILC 500 GeV and CLIC 3 TeV)

Parameter	Symbol [unit]	ILC	CLIC
Centre of mass energy	E_{cm} [GeV]	500	3000
luminosity	L [$10^{34}\text{cm}^{-2}\text{s}^{-1}$]	1.8	6
Luminosity in peak	$L_{0.01}$ [$10^{34}\text{cm}^{-2}\text{s}^{-1}$]	1	2
Gradient	G [MV/m]	31.5	100
Particles per bunch	N [10^9]	20	3.72
Bunch length	σ_z [μm]	300	44
Collision beam size	$\sigma_{x,y}$ [nm/nm]	474/5.9	40/1
Vertical emittance	$\epsilon_{x,y}$ [nm]	35	20
Bunches per pulse	n_b	1312	312
Distance between bunches	Δz [mm]	554	0.5
Repetition rate	f_r [Hz]	5	50

The CLIC strategy:

- Align components (10 μm over 200m)
- Control/damp vibrations (from ground to accelerator)
- Measure beams well – allow to steer beam and optimize positions
- Algorithms for measurements, beam and component optimization, feedbacks
- Tests in small accelerators of equipment and algorithms (FACET at Stanford, ATF2 at KEK, CTF3, Light-sources)






ATF/ATF2 Collaboration

Courtesy, N. Terunuma

Nano-beams



To develop nano-beam tech.


- Key for the Luminosity
- 6 nm beam at IP (ILC)



ATF2: Final Focus Test Beamline

Goal 1: establish "small beam" tech.

Goal 2: "stabilize beam position"



1.3 GeV S-band Electron LINAC (~70m)

A. Yamamoto, 171106



Progress in FF Beam Size and Stability at ATF2

Goal 1:
Establish the ILC final focus method with same optics and comparable beamline tolerances

- ATF2 Goal: 37 nm → ILC 6 nm
- Achieved 41 nm (2016)

Goal 2:
Develop few nm position stabilization for the ILC collision by feedback

- FB latency 133 nsec achieved (target: < 300 nsec)
- position jitter at IP: 210 → 67 nm (2015) (limited by the BPM resolution)



ILC Candidate Location: Kitakami, Tohoku



High-way

Oshu

Express-Rail

Ofunato

Sendai


Ichinoseki

IP Region


Kesen-numa



ILC Layout




Parameters	Value
C.M. Energy	500 GeV
Peak luminosity	$1.8 \times 10^{34} \text{ cm}^{-2}\text{s}^{-1}$
Beam Rep. rate	5 Hz
Pulse duration	0.73 ms
Average current	5.8 mA (in pulse)
E gradient in SCRF acc. cavity	$31.5 \text{ MV/m} \pm 20\%$ $Q_0 = 1\text{E}10$



ILC: SCRF



- Ultra-high Q_0 (10^{10})
 - Almost zero power (heat) in cavity walls (in SC RF the main efficiency issues related to fill factors and cryogenics)
 - Standing wave cavities with low peak power requirements
 - Long beam pulse (~ 1 ms) - favorable for feed-backs within the pulse train
- Low impedance
 - beam generates low “wakefields”
 - relatively large structures (1.3 GHz)




SCRF Accelerators Advances ... 2010 ~

Courtesy, H. Padamsee

Project	Notes	# cavities
CEBAF-JLAB (US)	Upgrade 6.5 GeV => 12 GeV electrons	80
XFEL-Hamburg (EU)	18 GeV electrons – for Xray Free Electron Laser – Pulsed)	840
LCLS-II – SLAC (US)	4 GeV electrons –CW XFEL (Xray Free Electron Laser)	300
SPIRAL-II (France)	30 MeV, 5 mA protons -> Heavy Ion	28
FRIB – MSU 8US)	500 kW, heavy ion beams for nuclear astrophys	340
ESS (Sweden)	1 – 2 GeV, 5 MW Neutron Source ESS - pulsed	150
PIP-II–Fermilab (US)	High Intensity Proton Linac for Neutrino Beams	115
ADS- (China, India)	R&D for accelerator drive system	> 200
Globally Int. Effort		> 2000

Worldwide SRF Collaboration



European XFEL

Americas, LCLS-II

ILC-SRF technology

Asia,
PAPS@IHEP CFF/STF@KEK




Progress:

- 2013: Construction started
- 2016: E-XFEL Linac completion
- 2017: E-XFEL beam start

Note: ~ 1/10 scale to ILC-ML

1.3 GHz / 23.6 MV/m
500+4 SRF acc. Cavities
100+3 Cryo-Modules (CM)



A. Yamamoto, 171106


European XFEL SRF Linac Completed

Courtesy: H. Weise

The E-XEL

Progress:
 2013: Construction started
 ...
 2016: E-XFEL Linac completion
 2017: E-XFEL beam start



1.3 GHz / 23.6 MV/m
800+4 SRF acc. Cavities
100+3 Cryo-Modules (CM)
 1/10 scale to LC-ML




Courtesy: D. Reschke, N. Walker, C. Pagani

A. Yamamoto, 71106

European XFEL: SRF Cavity Performance



After Retreatment:
E-usable: 29.8 to 5.1 (MV/m)
 (RI): E-usable 31.2 to 5.2 (MV/m) w/ 2nd P
 (EZ): E-usable 28.6 to 4.8 (MV/m) w/ CP (instead of 2nd P)




A. Yamamoto, 71106

ILC Parameters **demonstrated**

Characteristics	Parameter	Unit	Demonstrated
<u>Nano-bam:</u>			
ATF-FF equiv. beam size (y)	37 (reaching 41)	nm	KEK-ATF
ILC-FF beam size (y)	5.9 (correspond. 7)	nm	
<u>SRF:</u>			
Average accelerating gradient	31.5 ($\pm 20\%$)	MV/m	DESY, <u>FNAL</u> , JLab, Cornell, KEK,
Cavity Q_0	10¹⁰		
(Cavity qualification gradient	35 ($\pm 20\%$)	MV/m)	
Beam current	5.8	mA	DESY-FLASH), KEK-STF
Number of bunches per pulse	1312		DESY
Charge per bunch	3.2	nC	
Bunch spacing	554	ns	
Beam pulse length	730	ms	DESY, KEK
RF pulse length (incl. fill time)	1.65	ms	DESY, KEK, FNAL
Efficiency (RF→beam)	0.44		
Pulse repetition rate	5	Hz	DESY, KEK



ILC SC RF global integration model



ILC since the TDR in 2012-13: Technical focus and changes



Site specific studies

Technical developments for most accelerator systems - high Q improvements for example

E-XFEL at DESY successfully constructed and put into operation – a key technology demonstration


Recent proposal to start with an initial energy of 250 GeV ([physics impact report](#)) – key issues:

- Higgs precision depends significantly on HiLumi performance and theory assumptions ([link](#))
- Below $t\bar{t}$ threshold
- Reduced search capabilities

Nevertheless, provides impressive precision, and remains upgradable.


TDR costs of ~8 BILCU for 500 GeV (ILCU = 2012 US\$ estimate used in the TDR) can be reduced by up to ~40%

Options for ILC Staging at 250GeV





Options	Gradient [MV/m]	E_{CM} [GeV]	Total E_{CM} Margin	n	Space margin	Reserved tunnel	Total tunnel
TDR update	31.5	500	2%	10	1,473 m	0 m	33.5 km
Option A		250	6%	6	583 m	0 m	20.5 km
Option B				6&8		3,238 m	27 km
Option C				6&10	6,477 m	33.5 km	
Option A'	6			0 m	20.5 km		
Option B'	35	250	6%	6&8	1,049 m	3,238 m	27 km
Option C'				6&10	6,477 m	33.5 km	

Status and Prospect for ILC




Compact Linear Collider (CLIC)



- 380 GeV - 11.4 km (CLIC380)
- 1.5 TeV - 29.0 km (CLIC1500)
- 3.0 TeV - 50.1 km (CLIC3000)




CLIC layout, power generation




Drive-beam (low energy, high intensity, long pulses) created by klystrons




t=00.01 ns



Drive beam time structure initial



Drive beam time structure final



First stage energy ~ 380 GeV

Parameter'	Unit'	380'GeV'	3'TeV'
Centre of mass, energy,	TeV,	0.38,	3,
Total, luminosity,	$10^{34} \text{cm}^2 \text{s}^{-1}$,	1.5,	5.9,
Luminosity, above, 99%, of, vs,	$10^{34} \text{cm}^2 \text{s}^{-1}$,	0.9,	2.0,
RepeE Eon, frequency,	Hz,	50,	50,
Number, of, bunches, per, train,		352,	312,
Bunch, separaEon,	ns,	0.5,	0.5,
AcceleraEon, gradient,	MV/m,	72,	100,
Site, length,	km,	11,	50,


Let us look at three challenges:

- High-current drive beam bunched at 12 GHz
- Power transfer + main-beam acceleration
- ~100 MV/m gradient in main-beam cavities

CLIC Test Facility (CTF3)



DELAY LOOP



COMBINER RING

CLEX



DRIVE BEAM LINAC




TBL




Two Beam Module

- Produced high-current drive beam bunched at 12 GHz




28A



Arrival time
stabilised
to 50 fs



- Demonstrated two-beam acceleration







31 MeV = 145 MV/m



Status

- Achieved 100 MV/m gradient in main-beam RF cavities




Acc. Structures TD24&26 – new baseline optimised and alternatives for manufacturing and cost


Baseline: Machines disks, damping structures, bonding steps



3 TeV structure CLIC G* (optimised)




Rectangular (manufacturing)



SwissFEL Assembly (brazing)




Halves: SLAC/CERN





- 104 x 2m-long C-band structures (beam \rightarrow 6 GeV @ 100 Hz)
- Similar μm -level tolerances
- Length \sim 800 CLIC structures



Industrial considerations (example)



Bodycote (FR)
Reuter (DE)
TMD (UK)



SWISSto12 (CH)
3T RPD (UK)
Concept Laser
(DE)
INITIAL (FR)
Protoshop (DE)



VDL (NL)
LT-Ultra (DE)
Yvon Boyer (FR)
DMP (ES)
Morikawa (JP)
KERN (DE)



Thermocompact (FR)
BACMI (FR)
Multivalent (NL)



CINEL (IT)
VDL (NL)
BACMI (FR)
CECOM(IT)
Reuter (DE)
Nihon (JP)
COMEB (IT)
Viztrotech (KR)



Thales (FR)
CPI(US)
Toshiba (JP)






Scandinova (SE)
Jema (ES)
Picatron (CH)

 Compact Linear Collider

Cost and Power


Table 11: Value estimate of CLIC at 380 GeV centre-of-mass energy.

	Value [MCHF of December 2010]
Main beam production	1245
Drive beam production	974
Two-beam accelerators	2038
Interaction region	132
Civil engineering & services	2112
Accelerator control & operational infrastructure	216
Total	6690



- Radio-frequency
- Magnets
- Cooling
- Ventilation
- Instrumentation & Controls
- Interaction area & experime

CERN energy consumption
2012: 1.35 TWh



A cost of ~6 BCHF and power ~200 MW are “reasonable” values
→ Continue work on modules, RF and CE for costs; for power RF and magnets

CLIC roadmap

2013 - 2019 Development Phase

Development of a Project Plan for a staged CLIC implementation in line with LHC results; technical developments with industry, performance studies for accelerator parts and systems, detector technology demonstrators

2020 - 2025 Preparation Phase

Finalisation of implementation parameters, preparation for industrial procurement, Drive Beam Facility and other system verifications, Technical Proposal of the experiment, site authorisation

2026 - 2034 Construction Phase

Construction of the first CLIC accelerator stage compatible with implementation of further stages; construction of the experiment; hardware commissioning

2019 - 2020 Decisions

Update of the European Strategy for Particle Physics; decision towards a next CERN project at the energy frontier (e.g. CLIC, FCC)

2025 Construction Start

Ready for construction; start of excavations

2035 First Beams

Getting ready for data taking by the time the LHC programme reaches completion





Technical activities – examples



Technical Developments are motivated by several possible reasons – and are now quite mature:


- Key components for system-tests (example magnets, instrumentation, modules)
- Critical for machine performance (example alignment, stabilization, damping ring studies)
- Aimed at cost or power reduction (example magnets, klystrons, modules)



Information about some relevant suppliers and subcontractors participating to prototypes procurement for the CLIC Magnets R&D phase

Note: majority of coils and of other components manufacturing, magnet assembly, was done by CERN apart for the DBQ magnets (EM and PM versions).

1) Main Beam Quadrupoles. 4 prototypes procured: 3 Type1 (the shorter), 1 Type4 (the longer)



Relevant procurements:

- Coils: TESLA Engineering LTD, Storrington, West Sussex - UK
- High Precision quadrants machining: DMP 20850 Mendara, Gipuzkoa - ES

2) Drive Beam Quadrupoles (EM version): 3 prototypes procured by Daresbury Laboratory



Relevant manufacturers:


- Complete manufacturing: Danfysik A/S 2630 Taastrup, Denmark

3) Drive Beam Quadrupoles (PM version): 2 prototypes procured by Daresbury Laboratory



Relevant manufacturers:
- Design: PM
- High precision machining: SEN
- TSV
- Mc

5) Final Focus Quadrupole QD0: 1 prototype procured



Relevant manufacturers:

- PM blocks, Permendur EDM machining: Vacuumschmelze GmbH & Co. KG, Hanau - D

4) Main Beam Steering Dipoles: 2 prototypes procured




6) Final Focus Sextupoles SD0: (1 prototype procurement on-going)



Relevant manufacturers:

- Permendur and PM blocks procurement: VDL Groep BV, Eindhoven - NL


7) Octupoles for ATF facility at KEK, Japan: 2 magnets procured



Relevant manufacturers:

- Coils: S.E.F. Sarl, Labège - F
- Iron Yokes EDM Machining: Röttgers Værktøj A/S Odense - DK

Towards TeV beams with new technology ?



- 1.7 GeV energy gain in 30 cm of pre-ionized Li vapor plasma.
- 2% energy spread
- Up to 30% wake-to-bunch energy transfer efficiency (mean 18%).


A possible witness beams:

Electrons: 10^{10} particles @ 1 TeV
 ~few kJ

Existing driver beams options :

- Lasers: up to 40 J/pulse
- Electron driver: up to 60 J/bunch
- Proton driver: SPS 19 kJ/bunch, LHC 300 kJ/bunch

While GeV acceleration in plasmas has been demonstrated for with both lasers and electron beams, reaching TeV scales requires **staging** of many drivers and plasma cells. Challenging.



Current focus on “small scale” applications – for LCs a long way to go:


Electrons and Positrons, staging, energy efficiency, suitable beam-parameters and luminosity

However – disruptive technologies so (always) very important to pursue (and cost in this case likely less)

Ex. links LCs and FELs for CLIC(ILC shown already)

CERN	XBox-1 test stand	50 MW	Operational, connection to CLEAR planned
	Xbox-2 test stand	50 MW	Operational
	XBox-3 test stand	4x6 MW	Operational
Trieste	Linearizer for Fermi	50 MW	Operational
PSI	Linearizer for SwissFEL	50 MW	Operational
	Deflector for SwissFEL	50 MW	Design and procurement
DESY	Deflector for FLASHforward	6 MW	Design and procurement
	Deflector for FLASH2	6 MW	Design and procurement
	Deflector for Sinbad	tbd	Planning
Tsinghua	Deflector for Compton Source	50 MW	Commissioning
	Linearizer for Compton Source	6 MW	Planning
SINAP	Linearizer for soft X-ray FEL	6 MW	Operational
	Deflectors for soft X-ray FEL	3x50 MW	Procurement

Australia	Test stand	2x6 MW	Proposal submission
Eindhoven	Compact Compton Source, 100 MeV	6 MW	Design and procurement
Valencia	S-band test stand	2x10 MW	Installation and commissioning
KEK	NEXTEF test stand	2x50 MW	Operational
SLAC	Design of high-efficiency X-band klystron	60 MW	In progress
Daresbury	Linearizer	6 MW	Design and procurement
	Deflector	tbd	Planning
	Accelerator	tbd	Planning
Frascati	XFEL, plasma accelerator, 1 GeV	4(8)x50 MW	CDR
	Test stand	50 MW	Design and procurement
Groningen	1.4 GeV XFEL Accelerator, 1.4 GeV	tbd	NL roadmap, CDR



Eindhoven University led
SMART*LIGHT Compton Source

Key points

Two linear collider projects are being pursued (**ILC and CLIC**) – with large collaborative effort.

- **Both are mature, have a clear physics case, are (each) affordable** – and it is likely one will be built.
- Within 1-2 year the landscape in Japan and Europe can be expected to be clearer.

The developments (design, technical developments, tests of single elements or systems, industrial (pre)-productions – and also civil engineering, conventional systems, power and cost optimizations, are done **by international teams/collaborations**, usually led a major lab with special interest in the project but with world-wide participation since the technology developments and knowledge are transferable to other and/or **local projects**.

Linear accelerator technology and development are currently strongly taking part outside particle physics – very beneficial in both directions and easy to show societal impact

Any linear collider facility is likely to host many future machines. It can be **extended** – and/or equipped with new technology in the future ... but still a long way to go

Future accelerators in particle physics are today **cost and power limited** – don't scale energy unless you can scale down cost/GeV and maintain or increase luminosities

